

T SERIES
MAJOR

TC 5800 F



AC TRACTORS

Inspired by Mediterranean agriculture, this is a steering tractor (**51,5 hp** Yanmar engine) with different-size wheels for professional use. It is ideal for use in specialized applications on hillsides and mountains, offering the grip, handling and compact dimensions required to work on slopes and uneven terrain.

The **TC F Major** aims for maximum operator comfort: the grab handles on the rear fenders, useful when working on slopes, assist access to a spacious driving position free from obstacles and comfortable for drivers of any stature.



ANTONIOCARRARO.COM



N°1 SPECIAL TRACTORS

TECHNICAL DATA:

TC 5800 F

Frame	ACTIO™ integral oscillating frame • Unidirectional • Steering wheels • Different size wheels with all-wheel drive • Front and rear final drives	
Engine type	Supercharged diesel with common rail direct injection Emissions Standard: Stage 5 N° Cylinders: 4 - 16 Valves Rated rpm: 2600 Tank capacity (litres): 38.5	Power kW/CV (97/68/CE): 37.9/ 51,5 Max torque (Nm/rev): 168,2/1690
Transmission	24 speed synchronised gearbox: 12 FWD + 12 REV with shuttle	
PTO	Independent, mechanical control, standard 540 rpm and synchronised groundspeed	
Shaft	1 3/8" splined	
Rear linkage	Rear hydraulic lift with 3-point linkage Lifting capacity (kg): 2200 Oscillating lift arms and lateral stabilizer bars, Cat. 1; Category "C" adjustable rear tow hook	
Steering	Hydraulic 2 pistons	
Brakes	Service brakes: rear oil-immersed disc brakes with hydraulic control; Emergency and parking brake: transmission brake band	
Standard Features	<ul style="list-style-type: none"> • Mechanically-controlled front and rear • Adjustable driving seat with suspension • Safety belts • Adjustable rear tow hook • Front tow hook • Folding roll bar • Adjustable wheel discs • Horn • Lights and direction indicators • 3- and 7-pole electrical outlet sockets • Central control panel • Safe start switch • Digital speedometer • Battery disconnect • Provision for flashing light attachment 	
Optional	<ul style="list-style-type: none"> • Hydraulic lift with position and draft control • 540 and 1000 rpm PTO • Directable rear LED worklight • hydraulic system with single- and double-acting remote valves • Wheel ballasts • Tilt-adjustable steering column • Pneumatic seat suspension 	
Dimensions	with front wheels: 8,25-16	rear: 280/85 R20

